

Vert-X 32E - 8.5 ... 35V / 4 - 20mA / Single

32E5b799152499

**Technical datas**

Mechanical version	Magnetic actuator type 5
Mounting hole	Through-hole $\varnothing$ 4.4 mm with counter bore $\varnothing$ 8 mm/label side
Sensor principle	MH-C
Electrical angle	Special angle
Power supply voltage	24 VDC
Output signal	4 mA to 20 mA
Output characteristics	Single, positive gradient CCW
Electrical connection	Round cable, 3-pole
Length of cable	Special length

Electrical Datas

Measuring range	°	0...360
Indep. linearity (typ.)	% of measuring range	± 0.3
Max. hysteresis	°	0.1
Resolution	bit	12
Max. repeatability	°	0.1
Sample rate fast mode	kHz	(5)
Sample rate slow mode	kHz	1.66
System propagation delay fast mode	μ s	(800)
System propagation delay slow mode	μ s	4600
Max. temperature coefficient of output signal	ppm/K	100
MTTFd / MTBF		upon request
Power supply voltage (ohmic load at output = 0–0.5 kOhm)	VDC	13.5...35
Power supply voltage (ohmic load at output = 0–0.25 kOhm)	VDC	8.5...35
Current consumption without load (typ.) fast mode, per channel	mA	(19)
Current consumption without load (typ.) slow mode, per channel	mA	14
Ohmic load at output	k Ω / kOhm	0 ... 0.5
Max. capacitive load at output	nF	100
Reverse polarity protection of power supply		yes
Electrical connection		Round cable, 3-pole
Cross section of single wires	mm ²	0.56 (AWG20)
Redundancy possible		no

Mechanical Datas

Mechanical range	°	360 (continuous)
Protection rating		IP68/IP69K
Min. life	movements	no limitation
Operating & storage temperature	°C	-40...+85
EN 60068-2-6, vibration (Amax = 0.75 mm, f = 5–2,000 Hz)	g	20
EN 60068-2-27, shock	g	50

Standards

EN 55011, Emission (Cl. B)		
EN 61000-4-2, ESD (contact discharge / air discharge)	kV	± 4 / ± 8
EN 61000-4-3, Immersion HF radiated (80–1000 MHz/1.4–2.7 GHz)	V/m	30
EN 61000-4-4, Burst (on all lines)	kV	± 1

Features

- Non-contacting measuring method
- High protection rating IP68/IP69K
- Very long life
- High measurement accuracy
- Can be used in harsh environments (humidity, dampness, dust, vibrations, etc.)
- Magnetic loss detection (with safety flag)

Features MH-C

- Resolution 12 bit
- Lower price than MH-C2

Vert-X 32E - 8.5 ... 35V / 4 - 20mA / Single

32E5b799152499



EN 61000-4-5, Surge (lines to ground)	kV	±1
EN 61000-4-6, Immision HF conducted (0.15–80 MHz)	Vernf	10
EN 61000-4-8, Immision magnetic field (50 Hz)	A/m	300
Insulation resistance (500 VDC, 1 bar, 2s)	GOhm	20
Dielectric strength (VAC, 50 Hz, 1 min, 1 bar)	kV	1

Options


Custom modification of housing

Custom cable

Custom magnetic actuator

Special electrical angle between 30 and 360° (ex factory)

Extended operating range, axial (without safety flag)

**Operating range/Air gap (A)
Standard with Safety Flag**

- 1.4 ... 6.7mm

**Extended without Safety
Flag (Optional)**


- 0 ... 10.4mm

Features Safety Flag


- Detection of magnetic loss
- System shut-down in case of magnetic actuator out of valid operating range
- Recommended for safety relevant applications

Vert-X 32E - 8.5 ... 35V / 4 - 20mA / Single

32E5b799152499




Vert-X 32E5b



Vert-X 32E5d

Vert-X 32E - 8.5 ... 35V / 4 - 20mA / Single

32E5b799152499



Indep. linearity with radial misalignment (@360°)