

Vert-X 32E - 5V / PWM / Redundant**32E5b736245999****Technical datas**

Mechanical version	Magnetic actuator type 5
Mounting hole	Through-hole $\varnothing$ 4.4 mm with counter bore $\varnothing$ 8 mm/label side
Sensor principle	MH-C
Electrical angle	Electrical angle 360°
Power supply voltage	5 VDC
Output signal	PWM
Output characteristics	Redundant, crossed signal curves
Electrical connection	Special cable
Length of cable	Special length

Electrical Datas

Measuring range	°	0...360
Indep. linearity (typ.)	% of measuring range	± 0.3
Max. hysteresis	°	0.1
Resolution	bit	12
Max. repeatability	°	0.1
Sample rate fast mode	kHz	(5)
Sample rate slow mode	kHz	1.66
System propagation delay fast mode	μ s	(800)
System propagation delay slow mode	μ s	4600
Max. temperature coefficient of output signal	ppm/K	25
MTTFd / MTBF		upon request
Power supply voltage	VDC	5 ($\pm 10\%$)
Current consumption without load (typ.) fast mode, per channel	mA	(14)
Current consumption without load (typ.) slow mode, per channel	mA	9
Min. ohmic load at output	kOhm	10
Max. capacitive load at output	nF	1
PWM frequency	Hz	855 ($\pm 20\%$)
Reverse polarity protection of power supply		yes
Electrical connection		2x round cable, 3-pole
Cross section of single wires	mm ²	0.56 (AWG20)
Electrical connection redundant		Round cable, 6-pole, s
Cross section of single wires redundant	mm ²	0.25 (AWG24)

Mechanical Datas

Mechanical range	°	360 (continuous)
Protection rating		IP68/IP69K
Min. life	movements	no limitation
Operating & storage temperature	°C	-40...+85
EN 60068-2-6, vibration (Amax = 0.75 mm, f = 5–2,000 Hz)	g	20
EN 60068-2-27, shock	g	50

Features

- Non-contacting measuring method
- High protection rating IP68/IP69K
- Very long life
- High measurement accuracy
- Can be used in harsh environments (humidity, dampness, dust, vibrations, etc.)
- Magnetic loss detection (with safety flag)

Features MH-C


- Resolution of 12bit

Vert-X 32E - 5V / PWM / Redundant**32E5b736245999****Standards**

EN 55011, Emission (Cl. B)		
EN 61000-4-2, ESD (contact discharge / air discharge)	kV	$\pm 4 / \pm 8$
EN 61000-4-3, Immision HF radiated (80–1000 MHz/1.4–2.7 GHz)	V/m	30
EN 61000-4-4, Burst (on all lines)	kV	± 1
EN 61000-4-5, Surge (lines to ground)	kV	± 1
EN 61000-4-6, Immision HF conducted (0.15–80 MHz)	Vemf	10
EN 61000-4-8, Immision magnetic field (50 Hz)	A/m	300
Insulation resistance (500 VDC, 1 bar, 2s)	GOhm	20
Dielectric strength (VAC, 50 Hz, 1 min, 1 bar)	kV	1

Options

Custom modification of housing
Custom cable
Custom magnetic actuator
Sample rate in fast mode
Special electrical angle between 30 and 360° (ex factory)
Extended operating range, axial (without safety flag)

**Operating range/Air gap (A)
Standard with Safety Flag**

- 1.4 ... 6.2mm

**Extended without Safety
Flag (Optional)**

- 0 ... 10.4mm

Features Safety Flag


- Detection of magnetic loss
- System shut-down in case of magnetic actuator out of valid operating range
- Recommended for safety relevant applications

Vert-X 32E - 5V / PWM / Redundant


32E5b736245999



Vert-X 32E5b




Vert-X 32E5d



Vert-X 32E - 5V / PWM / Redundant

32E5b736245999



Indep. linearity with radial misalignment (@360°)