



Electrical Data		
Nominal resistance	kOhm	0.1 ... 2000
Resistance tolerance	%	±10
Independent linearity	% of meas. range	±2.0
Electrical angle	°	270
Temperature coefficient of the voltage divider	ppm/°C	100
Recommended wiper current	µA	max. 1
Max. wiper current in case of malfunction	mA	100
Power rating P	W/70°C	max. 2
Min. life (electrical)	cycles	50'000

Mechanical Data		
Mechanical range	°	300 / 272
Torque	Ncm	max. 1
Min. life (mechanical)	cycles	50'000
Operating temperature	°C	-25 ... +125
Storage temperature	°C	-40 ... +125
Protection class		IP54

Standards		
Insulating resistance (500 VDC, 1bar, 2s)	GOhm	10
Dielectric strength (VAC, 50Hz, 1min, 1bar)	kV	1.5
Vibration (Amax = 0.75mm, f = 30 ... 2000 Hz)	g	10
Shock (half sine pulse, 7 ms)	g	50

PC260 / 262

Applications

- Road roller

Features

- Small dimensions
- Linearity ±2 %
- High operating temperature

Options

- Special electrical angles
- Custom shafts design
- Custom bushing design

Errors and omissions excepted. Subject to change without notice. / State: 05.05.20

Contelec AG
 Portstrasse 38
 CH-2503 Biel/Bienne
 Phone +41 (0)32 3665600
 Telefax +41 (0)32 3665604
 sales@contelec.ch

CONTELEC
 A company of the Siedle-Group