

SAFETY DATA SHEET

Issue Date No data available

Revision Date 20-Mar-2015

REVISION NUMBER: 3

Product identifier**Product Name** 9637**Other means of identification****Product Code** 9637**Synonyms** None**Recommended use of the chemical and restrictions on use****Recommended Use** No information available.**Uses advised against** No information available**Details of the supplier of the safety data sheet****MANUFACTURED BY:**

VON ROLL USA, INC.

200 VON ROLL DRIVE

SCHENECTADY, NY 12306

BUSINESS: (518) 344-7100

EMERGENCY: (518) 395-3310

Emergency telephone number**Classification****OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

ACUTE TOXICITY - DERMAL	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Label elements**Emergency Overview****Danger****Hazard statements**

Harmful in contact with skin

Harmful if inhaled

Causes skin irritation

Causes serious eye irritation

May cause genetic defects

May cause cancer

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Flammable liquid and vapor

**Appearance** No information available**PHYSICAL STATE** Liquid**ODOR** No information available**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Wear eye/face protection
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/ ? /equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
 Specific measures (see ? on this label)
 Specific treatment (see ? on this label)
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 Call a POISON CENTER or doctor/physician if you feel unwell
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash before reuse
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other Information**

- Toxic to aquatic life with long lasting effects
- Toxic to aquatic life

Toxicity: Not determined

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	CAS No.	APPROX. WEIGHT PERCENT	TRADE SECRET
Xylene (Mixed Isomers) 1330-20-7	1330-20-7	10 - 30	

Solvent, Naphtha, Light Aromatic 64742-95-6	64742-95-6	5 - 10	
1,2,4-Trimethylbenzene 95-63-6	95-63-6	5 - 10	
Ethyl Benzene 100-41-4	100-41-4	1 - 5	
Solvent, Naphtha, Heavy Aromatic 64742-94-5	64742-94-5	1 - 5	
2-Butoxyethanol 111-76-2	111-76-2	1 - 5	
Cumene 98-82-8	98-82-8	1 - 5	
Naphthalene 91-20-3	91-20-3	0.1 - 1	

First aid measures

EYE CONTACT	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
SKIN CONTACT	Wash skin with soap and water.
Inhalation	Remove to fresh air.
INGESTION	Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Special Hazards:

None Known.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials None known based on information supplied.

Control parameters

Exposure Guidelines

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	ACGIH TLV	OSHA PEL-TWA	NIOSH IDLH
Xylene (Mixed Isomers) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	100	-
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-	-
1,2,4-Trimethylbenzene 95-63-6	TWA: 25 ppm	25 (1989)	TWA: 25 ppm TWA: 125 mg/m ³
Ethyl Benzene 100-41-4	TWA: 20 ppm	100	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-	-
2-Butoxyethanol 111-76-2	TWA: 20 ppm	50	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
Cumene 98-82-8	TWA: 50 ppm	50	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³
Naphthalene 91-20-3	TWA: 10 ppm S*	10	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³

Appropriate engineering controls

ENGINEERING CONTROLS: Exhaust ventilation.
Showers.
Eyewash stations.
Use in a well ventilated area.

Individual protection measures, such as personal protective equipment

Von Roll recommends evaluation and selection of appropriate engineering controls (such as ventilation and eyewash/safety shower) as well as appropriate personal protective equipment (such as respiratory protection, protective gloves, eye protection) for safely handling this material. The following guidelines should be considered in this process.

EYE PROTECTION:	Safety glasses with side shields (designed to ANSI standards). Goggles may be required based on application and processing of material. Splash Goggles.
GLOVES:	Neoprene gloves.
VENTILATION:	Use only in well ventilated area. Localized mechanical ventilation.
RESPIRATORY PROTECTION:	Use in a well ventilated area. Use approved NIOSH respiratory protection if TLV exceeded, or over exposure is likely. Cartridge respirator.
OTHER PERSONAL PROTECTION DATA:	Rubber apron or other chemical-resistant apron.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

Information on basic physical and chemical properties

PHYSICAL STATE	Liquid	ODOR:	AROMATIC
Appearance	No information available	ODOR THRESHOLD	UNKNOWN
DESCRIPTION:	AMBER	(PPM):	

<u>PROPERTIES</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point/freezing point	No information available	
Boiling point / boiling range	No information available	
Flash point	22.8 °C / 73 °F	
EVAPORATION RATE	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	7.0	
Lower flammability limit:	1.0	
VAPOR PRESSURE	No information available	
VAPOR DENSITY	No information available	
SPECIFIC GRAVITY	0.97	
Water solubility	No information available	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
DENSITY	No information available
Bulk density	No information available

REACTIVITY

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

CONDITIONS TO AVOID

Keep away from heat, sparks and flame.

Incompatible materials

Avoid contact with acidic, basic or oxidizing agents. Metal salts such as aluminum chloride.

Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide. Toxic fumes. Toxic metal fumes. Fumes of aromatic hydrocarbons.

Information on likely routes of exposure

PRODUCT INFORMATION	No data available
Inhalation	No data available.
EYE CONTACT	No data available.
SKIN CONTACT	No data available.
INGESTION	No data available.

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	Oral LD50	Dermal LD50	Inhalation LC50
Xylene (Mixed Isomers) 1330-20-7	= 3500 mg/kg (Rat) = 4820 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit) > 2000 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h > 5.04 mg/L (Rat) 4 h
Solvent, Naphtha, Light Aromatic 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
1,2,4-Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat) = 8970 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat) = 4820 mg/kg (Rat)	= 15400 mg/kg (Rabbit) > 2000 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h > 5.04 mg/L (Rat) 4 h
Solvent, Naphtha, Heavy Aromatic. 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	> 3577 ppm (Rat) 6 h = 39000 mg/m ³ (Rat) 4 h
Naphthalene 91-20-3	= 1110 mg/kg (Rat) = 490 mg/kg (Rat)	= 1120 mg/kg (Rabbit) > 20 g/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	ACGIH	IARC	NTP	OSHA
Xylene (Mixed Isomers) 1330-20-7	-	Group 3	-	-
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-	-	-

1,2,4-Trimethylbenzene 95-63-6	-	-	-	-
Ethyl Benzene 100-41-4	A3	Group 2B	-	X
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-	-	-
2-Butoxyethanol 111-76-2	A3	Group 3	-	-
Cumene 98-82-8	-	Group 2B	Reasonably Anticipated	X
Naphthalene 91-20-3	A3	Group 2A Group 2B	Reasonably Anticipated	X

Reproductive toxicity No information available.
STOT - single exposure No information available.
Aspiration hazard No information available.

Numerical measures of toxicity - PRODUCT INFORMATION

Toxicity: Not determined
 The following values are calculated based on chapter 3.1 of the GHS document .
ATEmix (oral) 5504 mg/kg
ATEmix (dermal) 1718 mg/kg mg/L

Ecotoxicity

48.91327% of the mixture consists of component(s) of unknown hazards to the aquatic environment

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	Acute Algae Toxicity:	Acute Fish Toxicity:	Crustacea
Xylene (Mixed Isomers) 1330-20-7	11: 72 h Pseudokirchneriella subcapitata mg/L EC50	13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50	0.6: 48 h Gammarus lacustris mg/L LC50 3.82: 48 h water flea mg/L EC50
Solvent, Naphtha, Light Aromatic 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
1,2,4-Trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through 7.72: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
Ethyl Benzene 100-41-4	1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 11: 72 h Pseudokirchneriella subcapitata mg/L EC50 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 9.6: 96 h Poecilia reticulata mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

Solvent, Naphtha, Heavy Aromatic 64742-94-5	2.5: 72 h <i>Skeletonema costatum</i> mg/L EC50	1740: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 19: 96 h <i>Pimephales promelas</i> mg/L LC50 static 2.34: 96 h <i>Oncorhynchus</i> <i>mykiss</i> mg/L LC50 41: 96 h <i>Pimephales promelas</i> mg/L LC50 45: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through	0.95: 48 h <i>Daphnia magna</i> mg/L EC50
2-Butoxyethanol 111-76-2	-	1490: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 2950: 96 h <i>Lepomis macrochirus</i> mg/L LC50	1698 - 1940: 24 h <i>Daphnia magna</i> mg/L EC50 1000: 48 h <i>Daphnia</i> <i>magna</i> mg/L EC50
Cumene 98-82-8	2.6: 72 h <i>Pseudokirchneriella</i> <i>subcapitata</i> mg/L EC50	6.04 - 6.61: 96 h <i>Pimephales</i> <i>promelas</i> mg/L LC50 flow-through 2.7: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 semi-static 4.8: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through 5.1: 96 h <i>Poecilia</i> <i>reticulata</i> mg/L LC50 semi-static	7.9 - 14.1: 48 h <i>Daphnia magna</i> mg/L EC50 Static 0.6: 48 h <i>Daphnia</i> <i>magna</i> mg/L EC50
Naphthalene 91-20-3	0.4: 72 h <i>Skeletonema costatum</i> mg/L EC50	0.91 - 2.82: 96 h <i>Oncorhynchus</i> <i>mykiss</i> mg/L LC50 static 5.74 - 6.44: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 1.6: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through 1.99: 96 h <i>Pimephales</i> <i>promelas</i> mg/L LC50 static 31.0265: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static	1.09 - 3.4: 48 h <i>Daphnia magna</i> mg/L EC50 Static 1.96: 48 h <i>Daphnia magna</i> mg/L EC50 Flow through 2.16: 48 h <i>Daphnia magna</i> mg/L LC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	Partition coefficient
Xylene (Mixed Isomers) 1330-20-7	2.77 - 3.15
Solvent, Naphtha, Light Aromatic 64742-95-6	-
1,2,4-Trimethylbenzene 95-63-6	3.63
Ethyl Benzene 100-41-4	3.118
Solvent, Naphtha, Heavy Aromatic 64742-94-5	2.9 - 6.1
2-Butoxyethanol 111-76-2	0.81
Cumene 98-82-8	3.55
Naphthalene 91-20-3	3.3

Other adverse effects

No information available

Waste treatment methods**Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Do not reuse container.

EPA HAZARDOUS WASTE DISPOSAL CODE:

D001, RQ = 100 lb / 45.4 kg.

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	RCRA Classification:	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene (Mixed Isomers) 1330-20-7	-	Included in waste stream: F039	-	U239
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-	-	-
1,2,4-Trimethylbenzene 95-63-6	-	-	-	-
Ethyl Benzene 100-41-4	-	Included in waste stream: F039	-	-
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-	-	-
2-Butoxyethanol 111-76-2	-	-	-	-
Cumene 98-82-8	-	-	-	U055
Naphthalene 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145 Included in waste stream: K022	-	U165

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Xylene (Mixed Isomers) 1330-20-7	-	-	-	-
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-	-	-
1,2,4-Trimethylbenzene 95-63-6	-	-	-	-
Ethyl Benzene 100-41-4	-	-	-	-
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-	-	-
2-Butoxyethanol 111-76-2	-	-	-	-
Cumene 98-82-8	-	-	-	-
Naphthalene 91-20-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	California Hazardous Waste Status
Xylene (Mixed Isomers) 1330-20-7	Toxic Ignitable

Solvent, Naphtha, Light Aromatic 64742-95-6	-
1,2,4-Trimethylbenzene 95-63-6	-
Ethyl Benzene 100-41-4	Toxic Ignitable
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-
2-Butoxyethanol 111-76-2	-
Cumene 98-82-8	Toxic Ignitable
Naphthalene 91-20-3	Toxic

DOT SHIPPING NAME: RESIN SOLUTION
DOT HAZARD CLASS: 3
DOT PACKING GROUP: PG II
DOT LABEL(S): FLAMMABLE LIQUID
UN/NA NUMBER: UN1866
PLACARDS: FLAMMABLE LIQUID
ICAO/IATA: 3, III
MARINE POLLUTANT: NONE
NMFC CLASSIFICATION: CLASS 55

International Inventories

TSCA	Does not comply
DSL/NDSL	Complies
EINECS/ELINCS	Does not comply
ENCS	Does not comply
IECSC	Does not comply
KECL	Does not comply
PICCS	Does not comply
AICS	Does not comply

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

ACUTE HEALTH HAZARD	No
FIRE HAZARD	No
Sudden release of pressure hazard	No
REACTIVE HAZARD	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene (Mixed Isomers) 1330-20-7	100 lb	-	-	X
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-	-	-
1,2,4-Trimethylbenzene 95-63-6	-	-	-	-
Ethyl Benzene 100-41-4	1000 lb	X	X	X
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-	-	-
2-Butoxyethanol 111-76-2	-	-	-	-
Cumene 98-82-8	-	-	-	-
Naphthalene 91-20-3	100 lb	X	X	X

CERCLA

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	Hazardous Substances RQs	CERCLA/SARA RQ
Xylene (Mixed Isomers) 1330-20-7	100 lb	RQ 100 lb final RQ RQ 45.4 kg final RQ
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-
1,2,4-Trimethylbenzene 95-63-6	-	-
Ethyl Benzene 100-41-4	1000 lb	RQ 1000 lb final RQ RQ 454 kg final RQ
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-
2-Butoxyethanol 111-76-2	-	-
Cumene 98-82-8	5000 lb	RQ 5000 lb final RQ RQ 2270 kg final RQ
Naphthalene 91-20-3	100 lb 1 lb	RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

US State Regulations**CALIFORNIA PROPOSITION 65**

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

HAZARDOUS PRODUCT COMPOSITION/CAS NUMBER	New Jersey Right-to-Know List:	MA Right to Know Law:	Pennsylvania Right to Know List
Xylene (Mixed Isomers) 1330-20-7	X	X	X
Solvent, Naphtha, Light Aromatic 64742-95-6	-	-	-
1,2,4-Trimethylbenzene 95-63-6	X	X	X
Ethyl Benzene 100-41-4	X	X	X
Solvent, Naphtha, Heavy Aromatic 64742-94-5	-	-	-

2-Butoxyethanol 111-76-2	X	X	X
Cumene 98-82-8	X	X	X
Naphthalene 91-20-3	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not Applicable

NFPA RATING:

HEALTH 2, FLAMMABILITY 3, INSTABILITY 0

HMIS CLASSIFICATION:

HEALTH *2, FLAMMABILITY 3, PHYSICAL HAZARD 0

Prepared By

Santino M. Cardella

Revision Date

20-Mar-2015

Revision Note

No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

END OF MSDS